

# **SEMI-AUTOMATIC DIGITAL DISPLAY**WHEEL BALANCER



#### smartSonar™

Automatic rim width detection using sonar sensors to avoid manual entry errors.



### easyWeight<sup>™</sup>

Take the guesswork out of weight placement; this pinpoint accurate system uses a laser to show the exact spot to place a weight to ensure precise balancing.



#### SPLIT WEIGHT MODE

This feature allows for accurate balancing with easy-to-follow manual procedures to hide the weights behind the spokes, preserving the wheel's visual presentation.



#### **SEMI-AUTOMATIC DATA ENTRY**

Hand-operated gauge arm with easyALU™ assisted rim data entry for diameter and distance. Touch the rim with the gauge arm to enter the rim dimensions and automatically select the weight balancing mode.

## **B500P**



## **TECHNICAL SPECIFICATIONS**

Max Wheel Diameter	42"   107cm
Max Wheel Weight	154 lbs.   70 kg
Max Rim Width	20"   51cm
Power Supply	230V 50/60Hz
Dimensions HxWxL	72"x34"x52"   183x87x131cm

#### STANDARD ACCESSORIES

- · Three Centring Cone Set (42-116mm)
- · Weight Pliers
- · Adhesive Weight Remover
- · Clamping Cone with **Rubber Cushion**
- · Calibration Weight
- 4 Storage Pegs
- Power Clamp<sup>™</sup> Sleeve

## **OPTIONAL ACCESSORIES**

- · Light Truck Kit Spacer and Cone (122-172mm)
- · Motorcycle Wheel Adaptor
- · Clamping Plate (200mm)
- · Set of 9 Low-Taper Centring Collets (52,5-122mm)
- Set of FP Quick Flange Plates

**johnbean**.com

· External Insulation Transformer



FIND A DISTRIBUTOR



