

# **TILT-TOWER**TYRE CHANGER



#### **TILT-TOWER**

The pneumatic Tilt-Tower post provides maximum clearance for installing the tyre on the turntable.



## ON-FLOOR BEAD BREAKER (PEDAL-OPERATED)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tyres.



#### **TOP-SIDE BEAD SEATER**

This ergonomic hand-held nozzle injects a high-speed blast of air into the tyre to raise the bead and seal the tyre to the rim.



# T5300B



### **TECHNICAL SPECIFICATIONS**

Max Rim Diameter	22"   56cm
Max Tyre Width	13"   33cm
Max Wheel Diameter	39"   100cm
Power Supply	400V 3ph 50Hz 5,5A
Air Pressure Required	116-174 PSI   8-12 bar
Dimensions HxWxD	63"x73"x35"   160x85x90cm

### STANDARD ACCESSORIES

- 1 kg Lube Bucket Holder
- Tyre Lever Wave Plus
- Plastic Protectors for Mounting Head

### **OPTIONAL ACCESSORIES**

- Lube Brush
- Plastic Rim Protector
- Plastic Tyre Protector
- · Smart Bead Spacer
- · Bead Clamp
- Plastic Protector for Bead Breaker Blade
- Bead Breaker Blade for Off-Road Wheels
- · Roller Board
- RF Plus Bead Pusher Tool
- Spacer for Bead Breaker. 20mm | 50mm | 70mm
- · Rod with Conical Roller
- RF Plus Bead Breaker Tool







GERMANY +49 8634 622 0 ITALY +39 05*22* 733 **4**11

