

# T5325B 2S

## CORE FEATURES PROFESSIONAL SERVICE

Built to get the job done, the John Bean® T5325B 2S combines all the helpful features you need to change tyres the right way.

Practical and simple to use, the T5325B 2S offers a tilt-tower design that provides ample clearance to load tyres onto the turntable. The T5325B 2S is equipped with PROspeed™ technology to automatically monitor torque and maintain optimum rotational speed while ensuring the safety of the tyre. Ergonomic and effective, the pedal-operated on-floor bead breaker makes quick work of traditional and high-aspect tyres. Pneumatic bead assist utilises a three-piece design that allows a single technician the ability to mount and demount challenging low-profile tyres. Simple to operate, yet highly effective, the top-side bead seater utilises compressed air to seal the tyre to the rim.

The T5325B 2S provides all the advanced features you need for your tyre changing service.



## TILT-TOWER TYRE CHANGER



### TILT-TOWER

The pneumatic Tilt-Tower post provides maximum clearance for installing the tyre on the turntable.



### PROspeed™

The innovative self-adjusting technology provides the optimum torque and maximises the rotation speed for safe, efficient operation.



### ON-FLOOR BEAD BREAKER (PEDAL-OPERATED)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tyres.



### TOP-SIDE BEAD SEATER

This ergonomic hand-held nozzle injects a high-speed blast of air into the tyre to raise the bead and seal the tyre to the rim.

*WHEN GOOD ENOUGH ISN'T ENOUGH, JB.*

**JohnBean**

# T5325B 2S



## PNEUMATIC BEAD ASSIST

Our three-piece Pneumatic Bead Assist features a top roller, pressing foot, and lifting disk, to make it simple for a single technician to mount and demount low-profile and high-performance tyres.

## TECHNICAL SPECIFICATIONS

Max Rim Diameter	24"   61cm
Max Tyre Width	13"   33cm
Max Wheel Diameter	39"   100cm
Power Supply	230V 1ph 50-60Hz 16A
Air Pressure Required	116-174 PSI   8-12 bar
Dimensions HxWxD	63"x73"x70"   160x185x178cm

## STANDARD ACCESSORIES

- 5 kg Lube Bucket Holder
- Lube Brush
- Bead Lever Plus
- Bead Lever Protector Plus
- Plastic Rim Protector: Clip-on Type
- Bead Breaker Blade Sleeve
- Alloy Rim Protector Kit for Centre Type Sliding Jaws - Front & Rear

## OPTIONAL ACCESSORIES

- Plastic Tyre Protector: Clip-on Type
- Smart Bead Spacer Tail
- Bead Clamp
- Bead Press Tool MX
- Bead Pressing Roller for M/D Tool
- Quick Exchange Device with Mounting Head
- Wheel Lift

FIND A DISTRIBUTOR



AUSTRIA  
+49 2641 24 5 24

FRANCE  
+33 134 48 58 78

GERMANY  
+49 8634 622 0

ITALY  
+39 0522 733 411



Snap-on® Total Shop Solutions offers a wide range of garage equipment solutions for workshops, garages, car dealers, and tyre shops, thanks to the specific solutions provided by its portfolio of premium brands. John Bean is a brand of TSS and is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2023 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. sswH22279 (EU en) 02/2023

