

HEAVY-DUTY TYRE CHANGER



MOBILE CONTROL UNIT

Wired remote control console allows one technician to safely monitor all tyre changing operations.



EXTREMELY WIDE CLAMPING RANGE

Clamping range for rims of 14" to 58" without extensions; long jaws accommodate rims of high offset.



ADJUSTABLE MOUNTING TOOL

The adjustable mount/demount with bead-breaker disk and lever tool rotates 180 degrees to work on both sides of the tyre.



PRESET TOOL CARRIAGE

The mount/demount tool travels from right to left of the tyre for bead-breaking and mount/demount operation.

T8058



TECHNICAL SPECIFICATIONS

Max Rim Diameter	58" 147cm
Max Tyre Width	99" 250cm
Max Wheel Diameter	99" 250cm
Power Supply	400V 3ph 50Hz
Dimensions HxWxD	80"x82"x118" 202x210x299cm

AUSTRIA +49 2641 24 5 24

STANDARD ACCESSORIES

- Wave Lever Plus
- Long Tyre Lever
- Standard Tyre Lever 20" | 50cm
- Mounting Clamp

OPTIONAL ACCESSORIES

- Clamp for Light Alloy Rims
- Earth Mover Clamp (OTR)
- Tubeless Roller







johnbean.com